

ASCO Solenoid Valve - EF8210G002 - N.C. Nitrile Rubber

Our Product Introduction

for more products please visit us on achieversinstruments.com

Basic Information

- Place of Origin: China
- Brand Name: ASCO
- Certification: ATEX
- Model Number: EF8210G002
- Minimum Order Quantity: 1
- Price: negotiate
- Packaging Details: carton
- Delivery Time: 5-8weeks
- Payment Terms: T/T
- Supply Ability: 100pcs per month



Product Specification

- Manufacturer: ASCO Valve
- Flow Rate: 4 Cv
- Fluid: Gas, Water, Air
- Function: Normally Closed
- Max. Pressure: 125/100 Psig
- Max. Temperature: 150°F
- Seal Material: NBR
- Actuator Type: 2-Way
- Highlight: **Asco Electric Solenoid Valve, Asco Electric Solenoid Valve, temperature rating valve**



More Images



Product Description

ASCO Solenoid Valve - EF8210G002 - N.C. Nitrile Rubber

Features

Lead-free versions are available to comply with Safe Drinking Water Act regulations and ANSI/NSF 372

Available in lead-free brass valves with a variety of press and expansion fitting options for a fast and flameless installation

Valves can be specified for hot water service to 210 ° F for in laundry, boiler and heat exchanger applications

Available with Explosion Proof Enclosures

RedHat II Standard: Types 3, 3S, 4, 4X. Explosion Proof Types 6, 6P, 7, and 9

Valve Actuation Solenoid

Body Material Brass

Media Air, Inert Gas, Water, Light Oil

Pipe / Port Size 1/2 "

Port Type NPTF

Function2 way - 2/2 Normally Closed

Flow 4 Cv

Voltage 24 AC, 110 AC, 115 AC, 12 DC, 12 to 24 DC Voltage Ranging, 120 AC, 120 DC, 125 DC Battery Charging, 208 AC, 220 AC, 230 AC, 24 DC, 24 to 120 AC/DC Voltage Ranging, 240 AC, 240 DC - 50/60, Uncommon voltages available upon request.

Max Differential / Max Operating Pressure Up to 200 psi

Operating Environment Indoor, Outdoor



Achievers Automation Limited



13828861501



joanna@achieversautomation.com



achieversinstruments.com

RM 509, 5/F, THE CLOUD, 111, TUNG CHAU STREET, TAI KOKTSUI, KOWLOON, HONG KONG