

# ASCO 8327B302 Solenoid Valve Manual Reset, Solenoid - Direct Acting

### **Basic Information**

Place of Origin: ChinaBrand Name: ASCOCertification: ATEX

Model Number: NFET8327B302

Minimum Order Quantity:

Price: negotiate
Packaging Details: carton
Delivery Time: 5-8weeks
Payment Terms: T/T

Supply Ability: 100pcs per month



### **Product Specification**

Manufacturer: ASCO Valve
 Min To Max Fluid -20 - 55 °C Temperature:

Function: 3/2 Universal
Pipe/Port Type & Size: NPTF 1/4
Coil Class: H

Voltage: 24 Volts DCOrifice Size: 5.7 MmProduct Weight: 2.65 Kg

Highlight: asco poppet solenoid valve,

manual reset poppet solenoid valve, manual reset asco electric solenoid valve



## More Images





### **Product Description**

#### ASCO 8327B302 Solenoid Valve

#### **Product Description**

The ASCO Series 8327B302 is a line of 3/2-way direct-acting solenoid valves requiring zero minimum operating pressure. Its balanced poppet construction permits high flows at minimum power levels, making it ideal for power plants, refineries, and chemical processing facilities. The valve's PTFE rider rings and graphite-filled seals reduce friction and eliminate sticking to provide exceptional service life. The 3/2-way direactacting solenoid valves are ideal for process valve piloting applications.

#### **Specifications**

Manual Reset, Solenoid - Direct Acting Valve Actuation

**Body Material** Stainless Steel Media Air|Water Pipe / Port Size 1/4" Port Type NPTF

Function

3 way - 3/2 Universal Flow (Cv) 0.45

125 DC Battery Charging, 110 AC, 12 DC, 120 AC, 120 DC, 208 AC, 24 AC, 24 DC, 240 DC, 250 DC Battery Charging, Voltage

48 DC, 480 AC, 6 DC | 50, 50/60, 60

Hazardous, Indoor, Outdoor Operating Environment

Standards / Regulations CSA, Type 1, Type 2, Type 3, Type 3S, Type 4X, Type 6, Type 6P, Type 7, Type 9, UL







13828861501



joanna@achieversautomation.com



achieversinstruments.com