ACHIEVERS **Achievers Automation Limited**

Festo NECU-M-S-D12G4-C2-ET Straight plug, M12x1, 4-pin, D-coded, shieldable

Basic Information

. Place of Origin: **CHINA** . Brand Name: Festo

NECU-M-S-D12G4-C2-ET Model Number:

Minimum Order Quantity:

• Price: Negotiable Packaging Details: carton . Delivery Time: Negotiable • Payment Terms: T/T

• Supply Ability: 100pcs per month



Product Specification

Manufacturer: Festo

Product No: NECU-M-S-D12G4-C2-ET

• Plug Coding:

• DC Operating Voltage

Range:

0 V ... 250 V

2.5 KV • Surge Resistance: • Approved Cable Diameter: 6 Mm ... 8 Mm

• Degree Of Protection: IP67 • Product Weight: 44.3 G

Highlight: Festo M12x1 straight plug,

4-pin D-coded Festo plug, shieldable Festo cylinder plug



More Images





Product Description

Festo NECU-M-S-D12G4-C2-ET Straight plug

Based on norm

EN 61076-2-101

EN 61984

Product weight

44.3 g

Electrical connection 1

Straight plug, M12x1, 4-pin, D-coded, shieldable

Plug coding

D

Electrical connection 2

Screw terminal, can be shielded

DC operating voltage range

0 V ... 250 V

Operating voltage range AC

0 V ... 250 V

Surge resistance

2.5 kV

Transmission characteristics

DIN EN 50173/CAT 5

Approved cable diameter

6 mm ... 8 mm

Connection cross section

0.14 mm² ... 0.75 mm²

Degree of protection

IP67

Ambient temperature

-25 °C ... 85 °C

CE marking (see declaration of conformity)

As per EU low voltage directive

UKCA marking (see declaration of conformity)

To UK instructions for electrical equipment

LABS (PWIS) conformity

VDMA24364-B2-L

Note on materials

RoHS-compliant

Contamination level

3

Corrosion resistance class (CRC)

1 - Low corrosion stress

Housing material

Die-cast zinc, nickel-plated

Material of pin contacts

Brass, gold-plated



13828861501

joanna@achieversautomation.com

achieversinstruments.com

RM 509, 5/F, THE CLOUD, 111, TUNG CHAU STREET, TAI KOKTSUI, KOWLOON, HONG KONG