Our Product Introduction



SICK GRTE18S-P2447 Photoelectric Sensor, 550mm, PNP, Proximity Diffuse, 10 to 30V, GR18S Series

Basic Information

. Place of Origin: Germany . Brand Name: SICK

GRTE18S-P2447 Model Number:

Minimum Order Quantity:

• Price: Negotiable Packaging Details: carton . Delivery Time: Negotiable • Payment Terms: T/T

• Supply Ability: 100pcs per month



Product Specification

• Functional Principle: Photoelectric Proximity Sensor • Dimensions (W X H X D): 18 Mm X 18 Mm X 38.1 Mm

· Optical Axis:

• Sensing Range: 10 Mm ... 400 Mm 1) • Type Of Light: Visible Red Light

• Wave Length: 650 Nm

• Highlight: SICK GRTE18S-P2447 photoelectric sensor,

PNP proximity diffuse sensor 550mm,

GR18S series sensor 10-30V



More Images







Product Description

SICK GRTE18S-P2447 | GR18 CYLINDRICAL PHOTOELECTRIC SENSORS

Product Overview

- GR18 series cylindrical photoelectric sensor
- Photoelectric proximity sensor functional principle (energetic functional principle detail)
- Cylindrical housing design (light emission), M18 x 1 thread diameter (housing), axial optical
- 5mm to 550mm max sensing range, 10mm to 400mm sensing range, visible red type of light
- PinPoint LED light source, Ø 9mm (400mm) light spot size (distance), PNP switching output
- Potentiometer, 270° adjustment, 650nm wave length, male connector M12, 4-pin connection type
- Supply voltage range from 10VDC to 30VDC, 30mA current consumption, plastic, PMMA optics material
- IP67 enclosure rating, light/dark switching mode
- ≤100mA max output current, <lt/>1,000µs response time, 500Hz switching frequency
- Dimension (W x H x D) is 18 x 18 x 38.1mm, ambient operating temperature range from -25°C to +55°C



Achievers Automation Limited



13828861501



joanna@achieversautomation.com



achieversinstruments.com

RM 509, 5/F, THE CLOUD, 111, TUNG CHAU STREET, TAI KOKTSUI, KOWLOON, HONG KONG