Our Product Introduction



MTL4546Y MTL Instruments Isolating **Driver**

Basic Information

. Place of Origin: UK/China MTL . Brand Name: HART · Certification: Model Number: MTL4546Y

• Minimum Order Quantity:

• Price: Negotiate • Packaging Details: carton • Delivery Time: stock • Payment Terms: T/T

• Supply Ability: 1000pcs per week



Product Specification

Manufacturer: MTL Instruments MTL4546Y • Product No: . Mounting Method: Other • IP-rating: IP20 • Shipping Weight: 1kg • Quality Guarantee: 1 Year



More Images





Product Description

MTL4546Y MTL Instruments Isolating Driver

MTL4546Y Isolating Driver, for 4–20mA HART® valve positioners with line fault detection, MTL 4500 Intrinsically Safe Isolators. The MTL4546 accepts a 4/20mA floating signal from a safe-area controller to drive a current/pressure converter (or any other load up to 800Ω) in a hazardous area. For HART valve positioners, the module also permits bi-directional transmission of digital communication signals. Process controllers with a readback facility can detect open or short circuits in the field wiring: if these occur, the current taken into the terminals drops to a preset level. The MTL4546C and the MTL4546Y are very similar to the MTLx546 except that they provide open circuit detection only (i.e. no short-circuit detection).

Depth 15.8 mm

Galvanic separation between input and output yes

Height 121.8 mm IP-rating IP20

Mounting method Other

Number of channels 1

Number of input ranges 4 mA ... 20 mA 1

Number of output ranges 0 mA ... 20 mA 0


Number of output ranges 0 V ... 10 V 0

Number of output ranges 4 mA ... 20 mA

Operation temperature -20...60 °C Rated supply voltage at DC 24...24 V

Type of electric plug connection Screw connection

Width 104.8 mm



Achievers Automation Limited

13828861501

joanna@achieversautomation.com

achieversinstruments.com

RM 509, 5/F, THE CLOUD, 111, TUNG CHAU STREET, TAI KOKTSUI, KOWLOON, HONG KONG