Our Product Introduction

Metric TMR31 Endress Hauser Instruments TMR31-A1BABBAX1AAA Compact **Thermometer**

Basic Information

. Place of Origin: Germany

. Brand Name: Endress Hauser

· Certification: **ATEX**

TMR31-A1BABBAX1AAA Model Number:

• Minimum Order Quantity:

• Price: Negotiable · Packaging Details: carton • Delivery Time: Negotiable

Payment Terms: T/T

. Supply Ability: 100pcs per month



Product Specification

. Measuring Principle: Resistance Temperature Detector

• Insert / Probe: Pipe Version, Isolated Wires, Not Flexible

 Outer Diameter Protection 4,00 Mm (0,16") 6,00 Mm (0,24")

Tube / Insert:

Material Protection Tube/

Thermowell:

1.4404 (316L)

. Tip Shape: Straight

• Surface Roughness Ra: 0,8 μm (32 μin.)

• Highlight: metric Endress Hauser Instruments,

TMR31 Endress Hauser Instruments,

Compact thermometer



More Images





Product Description

Endress Hauser TMR31-A1BABBAX1AAA Compact thermometer Field of application

With cost efficiency, optimal use of space, reliable operation, easy installation and commissioning the TMR31 fulfills the requirements of modern process measurement technology. Vibration-proof integrated thin-film sensors guarantee highest operational safety at the fastest response times.

The TMR31 compact thermometers are used to measure temperatures from -50 °C to +150 °C (-58 °F to +302 °F), or up to +200 °C (+392 °F) with neck. The most common installation locations are tanks and pipes. TMR31 with process connections for general applications.

Potentiometric

Measuring principle
Resistance Temperature Detector

Characteristic / Application metric style compact temperature probe fast response time threaded process connection with or without neck

Thermowell / protection tube without (not intended to use with thermowell)

Insert / probe pipe version, isolated wires, not flexible

Outer diameter protection tube / Insert 4,00 mm (0,16") 6,00 mm (0,24")

Max. immersion length on request up to 600,00 mm (23,62")

Material protection tube/ thermowell 1.4404 (316L)

Process connection male thread: G1/4" G1/2" NPT1/4" NPT1/2" M14x1.5 M18x1.5 BSPT R1/2"

Tip shape straight

Surface roughness Ra 0,8 µm (32 µin.)

Operating temperature range PT 100: -50 °C ...200 °C (-58 °F ...392 °F)

Max. process pressure (static) at 20 °C: 100 bar (1.450 psi)

class A acc. to IEC 60751

Response time t50 = 1 s t90 = 2 s

Integration head transmitter no (4...20mA Signal)

Certification Marine approval UL 3111-1



Below are the TOP BRANDS we handle in the past 12 years:

| Manufacture | Products | |
|-----------------|---|--|
| Bently Nevada | 3500 Vibration Monitoring System | |
| | 3300 Proximity Probes, Sensors & Transducer Systems | |
| ALLEN BRADLEY | Industrial Control Products | |
| Pepperl-Fuchs | Industrial Sensors & Isolated Barrier | |
| MTL Instruments | Isolated Barrier | |
| Endress+Hauser | Flow, Level, Liquid Analysis Instrument | |
| YOKOGAWA | DCS & Field Instruments & Process Analyzers | |
| TE | Dynamic Products | |
| Georg Fischer | Piping System | |
| SMC | controls, process, and Industrial products | |
| SICK | Laser Sensor | |
| FESTO | Pneumatic & Electric Automation Product | |
| Rosemount | Analytical Products | |
| ASCO | Solenoid Valves | |
| IFM | Sensors & Controllers | |
| SCHMERSAL | Safety switches & Safety Systems | |
| ABB | V18345 Valve Positioner | |
| SIEMENS | PLC modules & Transmitter | |
| FISHER | DLC3100 Digital Level Controller | |
| TELEDYNE | Oxygen Sensor & Fuel Cell | |
| DETCON | Gas Detection Products | |
| HONEYWELL | Switches & Transmitter | |
| VEGA | Level Measurement Products | |
| AUMA | Electric Actuators and Gearboxes | |
| YASKAWA | Industrial Ac Drives | |

| BECKHOFF | Controllers & I/O Modules | |
|--|---------------------------|--|
| BALLUFF | Linear Position Sensors | |
| B&R | PLC Module | |
| Phoenix Contact | Housing | |
| Harting | Connector Han | |
| For more product details, please visit our website: www.achievers-automation.com | | |

FAQ of Achievers

Q:Are the Products Genuine OEM Units?

A: These items have been certified by Achievers Automation Limited to be genuine OEM Units obtained through OEM or independent third-party channels.

Q:How will you arrange shipment?

A: We can arrange shipment based on your request. We have cooperated forwader who can arrange shipment via FedEx, DHL,TNT with good price.

Q:What is the warranty of goods?

A: One-year Warranty.

Achievers Automation Limited



13828861501



joanna@achieversautomation.com



achieversinstruments.com

RM 509, 5/F, THE CLOUD, 111,TUNG CHAU STREET, TAI KOKTSUI, KOWLOON,HONG KONG