Achievers Automation Limited achieversinstruments.com

2 Wire Endress Hauser Ultrasonic Level Transmitter Time Of Flight Prosonic FMU30-AAHEABGHF

Basic Information

• Place of Origin: Germany

Brand Name: Endress Hauser

Certification: ATEX

Model Number: FMU30-AAHEABGHF

• Minimum Order Quantity: 1

Price: Negotiable
Packaging Details: carton
Delivery Time: Negotiable
Payment Terms: T/T

• Supply Ability: 100pcs per month



Product Specification

Approval: Non-hazardous Area

• Display; Operation: Envelope Curve Display On Site; Push

Button

• Electrical Connection: Gland M20, IP68

• Process Connection: Thread ISO228 G2, PP

Gross Weight: 0.944 KilogramCountry Of Origin: Germany

• Highlight: 2 wire endress hauser ultrasonic level

transmitter

, IP68 endress hauser ultrasonic level transmitter

, FMU30-AAHEABGHF



More Images





Product Description

Endress Hauser Ultrasonic measurementTime-of-Flight Prosonic FMU30-AAHEABGHF

The range of applications extends from monitoring levels in sewage treatment plants and process water tanks to applications for loading, storage and buffer tanks. FMU30 ultrasonic sensor offers proven software algorithms and all warning and alarm messages are shown on the four-line plain text display and guarantee fast remedy of problems. The envelope curve can also be shown on the display. As the analysis results are displayed directly on-site, this ensures quick and accurate error diagnostics.

Potentiometric

Measuring principle

Ultrasonic

Characteristic / Application

Compact ultrasonic transmitter

Supply / Communication

2-wire

Accuracy

+/- 3 mm or +/- 0,2 % of set measuring range

Ambient temperature

-20 °C ... 60 °C

(-4 °F ... 140 °F)

Process temperature

-20 °C ... 60 °C

(- 4°F ... 140 °F)

Process pressure / max. overpressure limit

0.7 bar ... 3 bar abs

(10 psi ... 44 psi)

Main wetted parts

PP/EPDM

Application

Application

Max. measurement distance

Max. measurement distance

Communication

4...20 mA

Certificates / Approvals

ATEX, CSA C/US, IEC Ex, NEPSI

Options

Accessory Enclosed:

UNI flange 2" ... 4"

Application limits

Application limits

Process connection	G / NPT 1 1/2"
	G / NPT 2"
	Blocking distance
	1 1/2": 0.25 m (0.8 ft)
	2":0.35 m (1.15 ft)



Below are the TOP BRANDS we handle in the past 12 years:

Manufacture	Products
Bently Nevada	3500 Vibration Monitoring System
	3300 Proximity Probes, Sensors & Transducer Systems
ALLEN BRADLEY	Industrial Control Products
Pepperl-Fuchs	Industrial Sensors & Isolated Barrier
MTL Instruments	Isolated Barrier
Endress+Hauser	Flow, Level, Liquid Analysis Instrument
YOKOGAWA	DCS & Field Instruments & Process Analyzers
TE	Dynamic Products
Georg Fischer	Piping System
SMC	controls, process, and Industrial products
SICK	Laser Sensor
FESTO	Pneumatic & Electric Automation Product
Rosemount	Analytical Products
ASCO	Solenoid Valves
IFM	Sensors & Controllers
SCHMERSAL	Safety switches & Safety Systems
ABB	V18345 Valve Positioner
SIEMENS	PLC modules & Transmitter
FISHER	DLC3100 Digital Level Controller
TELEDYNE	Oxygen Sensor & Fuel Cell
DETCON	Gas Detection Products
HONEYWELL	Switches & Transmitter
VEGA	Level Measurement Products
AUMA	Electric Actuators and Gearboxes
YASKAWA	Industrial Ac Drives
BECKHOFF	Controllers & I/O Modules
BALLUFF	Linear Position Sensors
B&R	PLC Module
Phoenix Contact	Housing
Harting	Connector Han
For more product details, please visit our website: www.achievers-automation.com	

FAQ of Achievers

Q:Are the Products Genuine OEM Units?

A: These items have been certified by Achievers Automation Limited to be genuine OEM Units obtained through OEM or independent third-party channels.

Q:How will you arrange shipment?

A: We can arrange shipment based on your request. We have cooperated forwader who can arrange shipment via FedEx, DHL,TNT with good price.

Q:What is the warranty of goods?

A: One-year Warranty.





13828861501



joanna@achieversautomation.com



achieversinstruments.com

RM 509, 5/F, THE CLOUD, 111, TUNG CHAU STREET, TAI KOKTSUI, KOWLOON, HONG KONG