

84661-50 | Bently Nevada | Velomitor Interconnect Cable In Stock

Our Product Introduction

for more products please visit us on achieversinstruments.com

Basic Information

- Place of Origin: USA
- Brand Name: BENTLY
- Certification: ATEX
- Model Number: 84661-33
- Minimum Order Quantity: 1
- Price: Negotiable
- Packaging Details: carton
- Delivery Time: Negotiable
- Payment Terms: T/T
- Supply Ability: 100pcs per month



Product Specification

- Overall Jacket: PVC
- Connector A: Integral, Molded Female Connector
- Connector B: Tinned Copper Lugs
- Operating Temp.: -34 °C To 121 °C (-29 °F To 250 °F)
- Compatible Sensors: 9200 Series Seismoprobe®, 330500 XL Seismoprobe®
- Compatible Systems: Bently Nevada 3500, 3300, 2300 Monitoring Systems
- Highlight: **Bently Nevada proximity probe cable, Velomitor interconnect cable, Bently Nevada cable with warranty**



Product Description

84661-50 | Bently Nevada | Velomitor Interconnect Cable

Product Specifications

Attribute	Value
Overall Jacket	PVC
Connector A	Integral, Molded Female Connector
Connector B	Tinned Copper Lugs
Operating Temp.	-34 °C to 121 °C (-29 °F to 250 °F)
Compatible Sensors	9200 Series Seismoprobe®, 330500 XL Seismoprobe®
Compatible Systems	Bently Nevada 3500, 3300, 2300 Monitoring Systems



Bently Nevada is a global leader in industrial asset condition monitoring and protection, specializing in vibration, pressure, and speed measurement solutions for critical machinery. With over 60 years of expertise, the company serves industries including oil & gas, power generation, and mining.

Product Overview

The Bently Nevada 84661-50 is a robust, two-conductor, twisted pair, and shielded cable designed for reliable vibration monitoring in industrial machinery protection systems. Its construction features 22 AWG conductors and durable armor sheath for mechanical protection against crushing, abrasion, and cuts while ensuring excellent immunity to electrical noise.

Key Features

- Armored, 2-conductor cable for vibration transducers
- 22 AWG (0.5 mm²) twisted pair conductors
- Overall foil/shield and stainless steel armor
- PVC jacket with stainless steel armor
- Sealed female connector on one end, bare tinned lugs on the other
- Standard lengths available in specific increments
- Operating temperature range: -34°C to 121°C (-29°F to 250°F)

Technical Details

Product Line	Bently Nevada Asset Condition Monitoring
Series	84661 Armored Extension Cable
Model Number	84661-50
Primary Use	Connecting 9200/330500 Series Sensors to 3500/42M monitoring systems



Frequently Asked Questions

Q: Are the Products Genuine OEM Units?

A: These items have been certified by Achievers Automation Limited to be genuine OEM Units obtained through OEM or independent third-party channels.

Q: How will you arrange shipment?

A: We can arrange shipment based on your request. We have cooperated forwarders who can arrange shipment via FedEx, DHL, TNT with competitive pricing.

Q: What is the warranty of goods?

A: One-year Warranty.



Achievers Automation Limited



13828861501



joanna@achieversautomation.com



achieversinstruments.com

RM 509, 5/F, THE CLOUD, 111, TUNG CHAU STREET, TAI KOKTSUI, KOWLOON, HONG KONG